

# STRETCH HOOD

**Stretch Hood**, Quality and technical excellence, high stretch to ensure reliable performance in every application. Strong and versatile and available in large formats, they offer excellent pallet stability, with the strength to hold large loads securely in place.



## Characteristics

- It is made of Recyclable LDPE material with Coex technology.
- UV protection and antistatic additives can be applied.
- It can be produced in the desired color.
- It is an economical and safe pallet protector. It is a product designed to increase efficiency.
- It is used in automatic palletizing lines. It isolates your products on the pallet from the external environment.
- Heat is not required during application. It saves energy consumption.
- Provides high speed palletizing advantage.
- It provides optimum protection against dust, dirt and moisture and is also ideal for outdoor storage.
- High tear puncture resistance, high holding force ensures stable load securing throughout the entire logistics chain, from loading and transport to the end-user.
- Appropriate film thickness - from 80 to 200 microns and recipe are prepared according to the weight of the palletized product and the special requirements of the customer.

## Usage

Stretch hood is generally used by companies producing construction materials. It is suitable for use in products such as:

- **construction chemicals**
- **ceramics**
- **raw materials**
- **cement and glass**
- **thermo-sensitive products**
- **beverages**
- **etc.**

# CONTACT US

- **United Arab Emirates**

Abu Dhabi – Saeed Bin Ahmed Al Otaiba St – Al Massoud Building –  
Suite 1801 , 18th Floor , P.O. Box : 26010  
+971 2 627 7751  
[info@afi-intl.com](mailto:info@afi-intl.com)

- **Egypt**

Delta Towers, El Nasr Road, Nasr City, Cairo Governorate, Egypt  
+20 223493233  
[info@afi-intl.com](mailto:info@afi-intl.com)

- **United Kingdom**

61 Bridge Street, Kingston, United Kingdom, HR5 33D  
[info@afi-intl.com](mailto:info@afi-intl.com)